



US008947320B2

(12) **United States Patent**  
**King et al.**

(10) **Patent No.:** **US 8,947,320 B2**  
(45) **Date of Patent:** **Feb. 3, 2015**

(54) **METHOD FOR INDICATING LOCATION AND DIRECTION OF A GRAPHICAL USER INTERFACE ELEMENT**

(58) **Field of Classification Search**

None

See application file for complete search history.

(75) Inventors: **Bennett M. King**, San Diego, CA (US);  
**Thomas E. Kilpatrick, II**, San Diego,  
CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,133,898 A 10/2000 Ludolph et al.  
6,252,563 B1 \* 6/2001 Tada et al. .... 345/1.1

(Continued)

(73) Assignee: **QUALCOMM Incorporated**, San  
Diego, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 443 days.

FOREIGN PATENT DOCUMENTS

CN 1484068 A 3/2004  
CN 1575117 A 2/2005

(Continued)

(21) Appl. No.: **12/553,243**

(22) Filed: **Sep. 3, 2009**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2010/0066643 A1 Mar. 18, 2010

International Search Report—PCT/US2009/056288—International  
Search Authority, European Patent Office, Dec. 11, 2009.

(Continued)

**Related U.S. Application Data**

(60) Provisional application No. 61/095,225, filed on Sep.  
8, 2008.

*Primary Examiner* — Joseph Haley

(74) *Attorney, Agent, or Firm* — James R. Gambale, Jr.

(51) **Int. Cl.**

**G06F 3/14** (2006.01)  
**G06F 1/16** (2006.01)  
**G06F 3/0488** (2013.01)  
**H04M 1/02** (2006.01)

(57) **ABSTRACT**

In a particular embodiment, a method includes receiving a user input at a first display surface of an electronic device to move a graphical user interface element displayed at the first display surface. The electronic device includes a second display surface separated from the first display surface by a gap. The method also includes determining that at least a portion of the graphical user interface element is to be moved beyond an edge of the first display surface into the gap such that the at least a portion of the graphical user element will not be displayed at the first display surface. The method further includes displaying the at least a portion of the graphical user interface element at the second display surface based on a location and a direction of movement of the graphical user interface element at the first display surface.

(52) **U.S. Cl.**

CPC ..... **G06F 3/1446** (2013.01); **G06F 1/1616**  
(2013.01); **G06F 1/1641** (2013.01); **G06F**  
**1/1649** (2013.01); **G06F 1/1654** (2013.01);  
**G06F 1/1677** (2013.01); **G06F 1/1684**  
(2013.01); **G06F 1/1694** (2013.01); **G06F**  
**3/0488** (2013.01); **G06F 3/1454** (2013.01);  
**G06F 2200/1614** (2013.01); **G06F 2200/1635**  
(2013.01); **H04M 1/0216** (2013.01); **H04M**  
**1/0247** (2013.01); **H04M 2250/12** (2013.01)  
USPC ..... **345/1.1**; 345/173

**33 Claims, 46 Drawing Sheets**

